

# SAFETY DATA SHEET

**CLEANMOR** 

706

(SIMILAR TO OSHA FORM 174)

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name CleanMor 706

Reference Code MTEQ Product # 200

1.2 Uses and uses advised against

Use(s) RESIN SOAK REMOVER

1.3 Details of the supplier of the safety data sheet

Supplier name OMEGASONICS

 Address
 330 E. East St, Suite A, Simi Valley, CA 93065

 Telephone
 1-805-853-0876/Toll Free: 1-800-669-8227

Fax 1-805-583-0561

Email omegasonics@omegasonics.com

Website <u>www.omegasonics.com</u>

1.4 Emergency telephone number(s)

**Emergency** 1-800-535-5053 **International** 1-352-323-3500

#### 2. HAZARDS IDENTIFICATION

CLASSIFICATION: UN1760

SIGNAL WORD: DANGER

**SYMBOLS:** 

## **KEEP OUT OF REACH OF CHILDREN!**

HAZARD STATEMENT: Causes skin burn and serious eye damage.

May corrode aluminum and other amphoteric metals.

Do not use on anodized or polished aluminum.

PRECAUTION STATEMENT: Wear protective goggles, gloves, and clothing.

Wash contaminated areas with water. In case of contact consult a physician.

Wash hands after use.

GENERAL ADVICE: Follow instructions and use good hygienic practices.

EYES: In case of contact, wash eyes. Remove contact lenses. Consult a physician. SKIN: Wash skin with water until irritation stops. Wash clothes before reuse.

Consult a physician for severe burns.

INHALATION: Remove victim to fresh air.

INGESTION: Drink large amounts of water to dilute cleaner. Consult a physician immediately. Mucosal

damage can occur counter indicating gastric lavage.

STORAGE: Store in original container indoors between 40° and 100° F.

DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Unused product should be

1

disposed of as a hazardous waste.

OTHER HAZARD: None known.

OTHER INFORMATION: None.

10/2/2017



# SAFETY DATA SHEET

## **CLEANMOR**

(SIMILAR TO OSHA FORM 174)

**706** 

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS#	PERCENT	TLV
Potassium Hydroxide	1310-58-3	<30	3mg/m <sup>3</sup>

#### 4. FIRST AID MEASURES

**EYES** Wash with water until irritation stops. Consult a physician.

**INHALATION** Move victim to fresh air and make comfortable.

**SKIN** Remove contaminated clothes and wash skin with clean water until irritation subsides. In cases of

severe reaction consult a physician. Wash clothing before reuse.

**INGESTION** Drink copious amounts of water to dilute cleaner. Mucosal damage may counter indicate gastric

lavage. Consult a physician. Never give water or anything to an unconscious person.

OTHER None.

#### 5. FIRE HAZARD

NONE:	Water based product
FIREFIGHTING PROCEDURE:	N/A
EXPLOSION/REACTIVITY DATA:	Nonreactive and not explosive.

#### **6. ACCIDENTAL RELEASE MEASURES**

Contain spill and clean up excess liquid using a wet vac or mop. Dispose of waste in accordance with federal, state, and local regulations. Wash area to sewer in compliance with regulations.

## 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Use approved hygienic and safety practices when handling product. Wear appropriate protective goggles, gloves, and clothing. Have adequate ventilation to ensure safe usage.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in original sealed container indoors between 40° and 100° F and apart from reactive products.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:	3mg/m³ mist only	
PERSONAL PROTECTION:	Wear glasses, goggles, or face shield when handling product.	
	Chemical resistant gloves, aprons, and boots should be worn when handling product.	
RESPIRATORY PROTECTION:	Not necessary with normal ventilation.	
	In confined area provide ventilation to prevent vapor build up.	
HYGENIC PRACTICES:	Wash hands after using and before eating.	









# SAFETY DATA SHEET

## **CLEANMOR**

(SIMILAR TO OSHA FORM 174)

706

APPEARANCE: Clear amber liquid with a mild detergent odor.

BIOLING POINT 212° SPG 1.25

VAPOR PRESSURE 25mm PERCENT VOLITLE >70

EVAPORATION RATE 1(water=1) SOLUBILITY 100%

pH 14 VAPOR DENSITY N/A FLAMMABILITY Non-flammable REACTIVITY Stable

#### 10. STABILITY AND REACTIVITY

STABILITY:	Stable	REACTIVITY	Not reactive
HAZARDOUS POLYMERIZATION:	Will not occur	FLAMMABILITY	Water based non flammable
INCOMPATABLE MATERIALS:	Strong acids and oxidizers. Do not mix product with other products.		

#### 11. TOXICOLOGICAL INFORMATION

#### SYMPTOMS FOR ROUTES OF EXPOSURE

INHALATION: Mucosal irritation to nose and respiratory tract.

SKIN: Irritation and redness and possible chemical burns.

EYE CONTACT: Irritation and redness.

INGESTION: Chemical burns to mouth, throat, and stomach; pain, nausea, vomiting, and diarrhea.

#### 12. ECOLOGICAL INFORMATION

Product is water soluble, biodegradable, and non-toxic.

#### 13. DISPOSAL CONSIDERATIONS

Neutralize then sewer or landfill in accordance with local, state, and federal regulations. Unused product is considered a hazardous waste.

#### 14. TRANSPORT INFORMATION

Ship in DOT approved containers using approved transportation means.

## 15. REGULATORY INFORMATION

DOT: UN1760 CORROSIVE LIQUID NOS (POTASSIUM HYDROXIDE), 8, PGIII

## **16. OTHER INFORMATION**

NFPA Health 2	Flammability 0	Instability 0	Other		
GENERAL DISCLAIMER	Information provided is correct to the best of our knowledge at current time.				
	Since use of the product is out of the control of the supplier, no warranty for the suitability and				
	use of the product in an application is given or implied.				

3